

Hydrogen	LW351			CV414-SC	AUTO438		
	IN 350 bar	OUT 3 bar	CV 0.06	RATING 414 bar	OUT N/A bar	CV 0.06	
A875	H875			M875	RF1034		
	IN 700 bar	OUT 30 bar	CV 0.35 / 0.5	IN 700 bar	OUT 60 bar	CV 0.35 / 0.5	
LW438	LW-TS414			BP301	AVC/AVO690		
	IN 438 bar	OUT 20 bar	CV 0.06	RATING 150 bar	OUT 150 bar	CV 0.1	
BP010	BP300			BP-LF2KH	BP-LF540		
	RATING 10 bar	OUT 5 bar	CV 0.1	RATING 2,068 bar	OUT 2,068 bar	CV 0.1	
BP-LF691	BP-MF400			BP-MF401	BP-MF690 (05)		
	RATING 1034 bar	OUT 900 bar	CV 0.1 / 0.02	RATING 400 bar	OUT 200 bar	CV 3.0	
BP-MF691	BP-MF690 (15)			BP-MF691 (05)			
	RATING 690 bar	OUT 300 bar	CV 1.5	RATING 690 bar	OUT 690 bar	CV 0.5	

KEY

gas

liquid

MANUFACTURER

PRESSURE TECH LTD

Units 1-2, Graphite Way, Glossop, UK, SK13 1QH

T +44 (0)1457 899 307

E sales@pressure-tech.com

W www.pressure-tech.com

08 OCT 2026

Product Overview								
Analyser & Inst.	ACS101		ACS240		ACS310			
	auto-changeover		auto-changeover		auto-changeover			
	IN 300 bar	OUT 20 bar	CV 0.5	IN 300 bar	OUT 10 bar	CV 0.06		
	ACU310		CYL310					
	auto-changeover		cylinder assembly					
IN 300 bar		OUT 20 bar	CV 0.06	IN 300 bar	OUT 20 bar	CV 0.06		
IN 414 bar		OUT 35 bar	CV 0.06					
CYL540	LF240		LF310		MINI300			
cylinder assembly	compact		low-flow		low-flow			
IN 550 bar	OUT 414 bar	CV 0.1	IN 414 bar	OUT 10 bar	CV 0.06	IN 300 bar	OUT 100 bar	CV 0.06
TS310		TS311						
two-stage		two-stage						
IN 414 bar		OUT 25 bar	CV 0.06	IN 414 bar		OUT 20 bar	CV 0.06	
XHM410	XHS410		XHS411		XHR310			
heated manifold	single heated		single heated		electric heated			
IN 300 bar	OUT N/A	CV N/A	IN 414 bar	OUT 35 bar	CV 0.06	IN 414 bar	OUT 35 bar	CV 0.06
XHR310		XHR311						
steam heated		electric heated						
IN 414 bar		OUT 35 bar	CV 0.06	IN 414 bar		OUT 150 bar	CV 0.06	
Speciality Gas			SGA		SGM			
line regulator			semi-auto changeover		manual changeover			
IN 300 bar			OUT 50 bar	CV 0.1	IN 300 bar		OUT 50 bar	CV 0.1
SGL			SGP		DSV			
line regulator			point-of-use		diaphragm shut-off valve			
IN 300 bar			OUT 50 bar	CV 0.1	OPERATING 300 bar		CV 0.3	

Low-Flow			LF311			LF540			LF792			Hydraulic			LGC690			MF414H			HYD690											
			low-flow  IN 414 bar OUT 180 bar CV 0.06	low-flow  IN 690 bar OUT 414 bar CV 0.1	low-flow  IN 1034 bar OUT 1034 bar CV 0.1 / 0.3 / 0.05	logic control  IN 414 bar OUT 20 bar CV 0.3	medium-flow  IN 414 bar OUT 414 bar CV 2.0	hydraulic  IN 690 bar OUT 690 bar CV 0.06																								
Medium-Flow			MF101			MF230			MF231			MF210			HYD691			LF690			DF1034			LF691								
			medium-flow  IN 414 bar OUT 40 bar CV 0.5	medium-flow  IN 230 bar OUT 10 bar CV 1.0	medium-flow  IN 230 bar OUT 100 bar CV 1.0	medium-flow  IN 40 bar OUT 10 bar CV 1.8	hydraulic  IN 690 bar OUT 690 bar CV 0.06	low-flow  IN 690 bar OUT 690 bar CV 0.05 / 0.1 / 0.3	dual-flow  IN 1380 bar OUT 1380 bar CV 1.5 & 0.06	low-flow  IN 1380 bar OUT 1380 bar CV 0.05 / 0.1 / 0.3																						
High-Flow			MF301			MF400			MF401			MF414			Diving			BIBS100			LF310			LF540								
			medium-flow  IN 300 bar OUT 300 bar CV 2.0	medium-flow  IN 400 bar OUT 10 bar CV 2.0	medium-flow  IN 400 bar OUT 400 bar CV 2.0	medium-flow  IN 414 bar OUT 414 bar CV 2.0	negative-biased  RATING 50 bar OUT 30 bar CV 2.0	low-flow  IN 414 bar OUT 35 bar CV 0.06 / 0.15	low-flow  IN 690 bar OUT 414 bar CV 0.1																							
High-Flow			HF211			HF250			HF251			MF101D			MF300T			MF301D														
			high-flow  IN 210 bar OUT 200 bar CV 13.0	high-flow  IN 250 bar OUT 10 bar CV 7.0	high-flow  IN 250 bar OUT 200 bar CV 7.0	medium-flow  IN 300 bar OUT 40 bar CV 0.5	medium-flow  IN 300 bar OUT 25 bar CV 2.0	medium-flow  IN 300 bar OUT 300 bar CV 2.0																								
High-Flow			HF300			HF301			HF600			Subsea			SS-BP400			SS-COM301			SS231			SS414			SS690			SS691		
			high-flow  IN 300 bar OUT 10 bar CV 4.0	high-flow  IN 300 bar OUT 300 bar CV 4.0	high-flow  IN 600 bar OUT 600 bar CV 7.0	subsea  IN 400 bar OUT 10 bar CV 2.0	subsea  IN 300 bar OUT 50 bar CV 0.5	subsea  IN 230 bar OUT 35 bar CV 1.0	subsea  IN 414 bar OUT 250 bar CV 2.0	subsea  IN 690 bar OUT 690 bar CV 0.1	subsea  IN 1034 bar OUT 690 bar CV 0.1																					